

# Product Specification of Ashford

Our Ashford paving range offers a unique textured finish. Cushion top features and rounded edges are reminiscent of a traditional cobble. Especially suitable for gardens and pedestrian areas.



**Thickness:** 50mm

**Use:** Driveway (light vehicular use) & Footpaths— domestic paving

**Laying Patterns:** 3 Size Mix

**Spacing Nibs:** 1.5mm nibs

**Finishes & Colour:** Pillow top finish with 3 colour options

**Kerbs:** Complimentary kerb range available



Autumn



Juniper



Silver Grey

Product	Brick Size mm	Colours	No. per Sq.m	No. per Pack	Pack Size Sq.m	Pack Weight Kgs	No. Packs per Arctic	Sq.m per Arctic Load
50mm 3 Size Mix	225 X 150 X 50 150 X 150 X 50 112.5 X 150 X 50	Available in all colours	17* 14* 6*	170 140 60	10	1200	22	200

**Raw Materials:** Sand, Stone, Cement, Pigment

**Manufacturing Process:** Hydraulically Pressed

**Manufacturing Standards:** Manufactured to BS EN 1338

**Quality Systems:** All products undergo testing to standards of EN ISO 9011 and are covered by CE certification.

**Application:** Please refer to Health & Safety data sheets

**Installation:** Installed to BS 7533

**Performance Criteria:** Strength: >3.6MPa or 250N/mm