

PRODUCT DATA SHEET

Feb[®] Febmix[®] Plus

MORTAR PLASTICISER

PRODUCT DESCRIPTION

Feb[®] Febmix[®] Plus is a liquid ultra-stable 'micro' air-entraining mortar plasticiser designed to enhance the workability and freeze thaw resistance of brick and block laying mortars. Feb[®] Febmix[®] Plus may be used to replace lime, and is designed to maintain efficiency with variations in cement and aggregate sources.

USES

- Designed to be used as a mortar plasticising admixture in brick and block laying mortars
- 'Micro' air entraining properties reduce water demand and greatly reduce the likelihood of cracking and crazing
- Provides enhanced resistance to frost attack in both wet and hardened mortar state

CHARACTERISTICS / ADVANTAGES

- Ultra-stable bubble structure.
- Uniform air-entrainment structure.
- Works with most types of Portland Cement and difficult sands.
- Increased resistance to damage by freeze/thaw.
- Reduced segregation and bleed.
- Non corrosive to embedded metals.
- Increased working time.
- Easier and faster mortar spread.
- Can be used with P.F.A. containing mortars.

APPROVALS / STANDARDS

Feb[®] Febmix[®] Plus conforms to EN 934 Part 3(2009) specification for air-entraining (plasticising) mortar admixtures.

PRODUCT INFORMATION

Packaging	5L, 25L and 205L
Appearance / Colour	Red
Shelf Life	Two years when stored in accordance with the manufacturer's instructions
Storage Conditions	Store at moderate (5°C - 30°C) temperatures. Will freeze, but can be reconstituted by stirring after thawing. Stir before use.
Density	0.98 - 1.02 g/cm ³
pH-Value	11.5 - 13.5
Conventional Dry Material Content	2.62 - 4.42%
Total Chloride Ion Content	< 0.1% (w/w)
Substrate Temperature	Freezing point @ -2°C

APPLICATION INSTRUCTIONS

MIXING

In all cases, add to mix or to gauging water at an addition rate of 125ml to 250ml per 50kg cement, depending on the degree of plasticizing/entrainment required. Note: remember to reduce required quantity of water accordingly. One litre of Feb® Febmix® Plus added to a 200 ltr drum of gauging water will be sufficient for gauging approx. 4 x 50 kg cement for mortar or render mixes.

APPLICATION METHOD / TOOLS

Feb® Febmix® Plus may be either pre-mixed with the water or added directly into the mix at the same time as the water. NB: the superior plasticising qualities of Feb® Febmix® Plus will result in a significant reduction in water demands of any given mix.

Feb® Febmix® Plus can be used with other admixtures provided these are added separately to the mix. It can be used for all types of Portland Cement, including sulphate-resisting. It can also be used in sand mortars as a further precaution against frost.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

FebFebmixPlus-en-GBEVER-(05-2018)-1-1.pdf